

### General Description

Nippon Paint Wall Care Prevention Moisture Sealer has the characteristics of filling and sealing. It can penetrate into interior of wall, allowing the wall surface to be free from moisture and water penetration and effectively preventing the occurrence of leakage. It has excellent adhesion on cement wall, tile, granolith, old painted wall, etc.

### Features

- Low viscosity
- High solid content
- Easy application
- Weathering resistance
- Good adhesion
- Good penetration
- Water-based product and safe

### Recommended For

- Interiors and exteriors
  - Cement wall
  - Tile
  - Granolith

### General Information

Colour:	Transparent yellowish	Drying time: (at 25 °C)	Touch dry :30 mins Hard dry: 1 hrs
Type:	Acrylic polymer	Overcoat Time: (at 25 °C)	> 2 hrs
Finishes:	N/A	Full Curing (at 25 °C)	7 days
Application Method:	Brush / Roller	Specific Gravity: (at 25 °C)	1.082 ± 0.02
Theoretical Coverage:	10 m <sup>2</sup> /L/coat	Solid Content: (by volume)	>45%
Dilution:	No	Packing:	1L / 5L
Dry Film Thickness:	10~20µm	Shelf Life:	24 months in sealed original packaging stored at room temperature and shaded place.

# Nippon Paint Wall Care Prevention Moisture Sealer

## Technical Data

<u>Test</u>	<u>Test Method</u>	<u>Result</u>
VOC Content (g/L)	USEPA Method 24	<100

### Surface Preparation

All surface must be clean, dry and free from oil, grease, dirt, contaminants and loose materials. If wall cancer is appeared on the, the surface, surface must be cleaned with iron brush or sand paper.

- ✧ **Ensure fresh air ingress while applying and before dry done**
- ✧ **High humidity and cool temperature will result in longer drying time**

### Application Details

- For the application of interior wall, the application area needs to be slightly larger than the area of wall cancer in order to cover all affected area. Application for two times is recommended
- For the application of exterior wall, the application area should also be increased. Apply two to three times for filling the small pores of the wall in order to achieve the best sealing and waterproof performance.

### Limitations

Avoid painting when the temperature is below 5°C or the humidity is over 85%. Do not paint when raining and rain is expected during painting or drying process.

### Clean Up

Wash painting tools with water immediately after use.

### Safety Information

Keep out of reach of children. If medical advice is needed, get the product container or label at hand for easy reference.

Be aware of sanding dust / spray mist. Protective gloves, eye or face protection are highly recommended. Keep away from sparks, heat, open flames and any other ignition sources.

Eating, drinking and smoking should be prohibited in areas where the material is handled, stored and processed.

In case of eye contact, rinse immediately with plenty of water. For splashed skin, clean thoroughly with soap and water. Seek medical attention if indication persists.

If you experience difficulties on breathing, leave applied area and obtain fresh air. If difficulties continue, immediately get medical attention.

Product must always be stored in a ventilated, cool and dry place.

Tightly close product container after each use.

### Flash Point and Ignition Point

Flash Point: N/A

Ignition Point: N/A

Note: The information given applies to the product and its performance under specific test condition. Due to the varied circumstances beyond our control under which the product may be applied, for specific applications, please contact Nippon Paint Project Sales Department. We reserve the right to modify our product specification without prior notice.

For further enquiries, please call:

**Nippon Paint (H.K.) Co., LTD**

Tel: (852) 2699 9333

Fax: (852) 2602 8844

Website: <http://www.nipponpaint.com.hk>

